



The New Iridium 9505A Phone

Iridium has launched the new 9505A handset. The 9505A has the same features and functions as the 9505, as well as a similar form, look and feel as the 9505. Information on the changes from the 9505 to the 9505A is listed on the bottom half of this page.

Now smaller, lighter and more resistant to water, dust and shock than Iridium's previous offering, this newest addition to the Satellite Series (TM) portfolio is ideal for industrial or rugged conditions, yet appealing to the traveling professional.

Business, adventure, or pleasure, you can stay in touch across seas and time zones, in remote locations and on the go. One telephone number, through the use of a mini personal subscriber identity module (SIM) card, can help keep you connected.



Includes:

- Rechargeable Li-ion Battery
- AC Travel Charger
- DC Charger
- International Plug Kit
- Headset
- User Guide
- Antenna Adapter
- Portable Aux Antenna
- Lanyard
- Leather Holster

Features:

- Smaller and lighter than the Iridium 9500
- Packed with Features, yet Simple to Use
- Quick Access Interface
- Water, shock & dust resistant for rugged environments
- Data Capable - Use your satellite phone to transmit data with an optional RS232 adapter
- IrDA Port (for future applications)
- 21 Language Choices for Prompts



Security Financing Services, Inc.
www.securityfinserv.com
Contact: Eric Flores (832) 964-9495

Headset/Hands-free capability

Talk Time Features:

Provides up to 30 hours of standby time with standard battery

Provides up to 3.2 hours of talk time

Display:

4 x 16 character Illuminated Graphic Display

Calling Features:

Auto Redial Notification

Call Barring

Call Forwarding - Unconditional, mobile subscriber busy, subscriber not reachable

Clear Last Digit/Clear All Digits

Fixed Dialing

International Access Key Sequence (+ key)

Mailbox for Numeric & Text (160 characters)

Quick Access Interface

Selectable Keypad tone (3 choices)

Selectable Ringer tone (10 choices)

Keypad Disable

Two-way SMS capability

Unanswered Call Indicator

Volume Adjustment (earpiece or ringer)

Memory:

100 Alpha and Numeric Memory Storage

Last 10 Numbers Dialed

Name Storage

Memory Scroll by Location

32-Digit Number Capacity Phone Book

16-Digit Name Tag

One-Touch Dialing

Subscriber Identity Module Card (additional memory storage)

Visual/Alert Features:

Signal Strength Meter

Battery Meter (always shown in display)

Illuminated Keypad

Low Battery Warning

Status Review of Features

Visual Display of Volume Settings

Usage Control Features:

Automatic Display Call Timer

Automatic Lock

Call Restrictions

Display Call Timers (last call / total calls)

Display/Change Unlock Code

Subscriber Identity Module PIN Availability (security code)

Technical Specifications:

Dimensions

158L x 62W x 59D mm

Volume Under 375cc (22.9 ci)

Weight Under 375g (13.2 ounces)

Battery:

3.2 hrs Continuous Talk Time

30 hrs Standby Time

Other Details:

Temperature, normal conditions: +15 to +35 °C

Temperature, extreme conditions: -10 to +55 °C

Relative Humidity: 25 to 75 %

Air Pressure: 86 to 106 kPa

Storage Conditions

Storage Temperature Range: -40 to +85 °C

Humidity: 40 °C, 93% RH for 4 days

Thermal Shock (IEC60068-2-14), full functionality upon completion of test and allowing device to return to room temperature:

-25 °C to +70 °C, 5 cycles of 1 hour each